

View Online at <https://aerobasegroup.com/nsn/3120-01-247-6906>

Shank Diameter:

Between 0.4688 inches and 0.5312 inches

Shank Style:

Hollow, unthreaded

Overall Length:

Between 2.3480 inches and 2.4020 inches

Bore Diameter:

Between 0.1895 inches and 0.1900 inches

Lubrication Material:

Lubricant, dry film

Outer Member Outside Diameter:

Between 0.9900 inches and 1.0100 inches

Bore Center To Shank End Distance:

Between 1.8438 inches and 1.9062 inches

Outer Member Width:

Between 0.4330 inches and 0.4430 inches

Inner Member Width:

Between 0.5880 inches and 0.5930 inches

Shank Inside Diameter:

Between 0.3800 inches and 0.4000 inches

Shank Hole Length:

Between 1.1875 inches and 1.2800 inches

Static Radial Load Rating:

3715 pounds

Hardness Rating:

55.0 rockwell c inner member and 62.0 rockwell c inner member

Lubrication Feature:

Self-lubricating liner race liner

Functional Description:

Self-lubricating female rod end

Material:

Steel comp 630 outer ring

Material Specification:

Ams5634 uns s17400 assn standard single material response outer ring

Reference Data And Literature:

Mil-b-81935/2

Surface Treatment:

Passivate inner member

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses outer ring

Style Designator:

Ball type

Supplementary Features:

-65.0 degrees f to 325.0 degrees f temp range

Type/model Designation:

D-durallner

Specification Data:

78898-131830 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-b-81820 spec.