

View Online at <https://aerobasegroup.com/nsn/3120-01-253-3040>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/hexagon end and inspection hole

Overall Length:

2.0750 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Outer Member Outside Diameter:

Between 0.8900 inches and 0.9100 inches

Bore Center To Shank End Distance:

Between 1.6150 inches and 1.6350 inches

Outer Member Width:

Between 0.3220 inches and 0.3320 inches

Inner Member Width:

Between 0.4350 inches and 0.4370 inches

Shank Thread Length:

1.0000 inches

Inspection Hole Center To End Distance:

Between 0.4170 inches and 0.4570 inches

Shank Width Across Wrench Flats:

Between 0.4900 inches and 0.5020 inches

Thread Diameter:

0.3125 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

57.0 rockwell c inner member and 63.0 rockwell c inner member

Special Features:

Race insert id dry film lubricant per mil-I-8937; rod end body finish not for cres optional material; threads on shank optional thread classification unf-3b

Material:

Steel comp e52100 inner member or steel comp 440c inner member

Material Specification:

Mil-s-7420 military specification 1st material response inner member or ams-6440 assn standard 1st material response inner member or qq-s-763 federal specification 2nd material response inner member

Surface Treatment:

Cadmium rod end body and chromate rod end body or zinc rod end body and chromate rod end body

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification 1st treatment response rod end body or astm b633, type 2 assn standard 2nd treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-7420 spec.