## NSN 3120-01-254-4446

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-254-4446 Slot Width: 0.6000 inches first Slot Length: 0.9200 inches first **Overall Length:** 1.9400 inches **Body Outside Diameter:** Between 3.9880 inches and 3.9900 inches **Body Inside Diameter:** 3.7300 inches Left Internal Flange Hole Diameter: 3.6200 inches Left Internal Flange Width: 0.3200 inches **Lubricant Accommodation Style:** Grooved circular **Corner Shape:** Square all corners **Antirotation/lubrication Type And Quantity:** 2 slot **Surface Groove Location And Quantity:** 1 external **Special Features:** Od relieved left end to 3.75 inch dia; all surfaces parco-lubrited Material: Steel uns k23080 **Material Specification:** Ams 6427 assn standard single material response Style Designator: 17c-1 solid, plain, no outside flanges, internal flange one end **Test Data Document:** 81349-mil-i-6870 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A045a0