

View Online at <https://aerobasegroup.com/nsn/3120-01-256-9292>

Thread Class:

2a

Thread Direction:

Left-hand

Shank Style:

Internally threaded

Overall Length:

Between 1.5520 inches and 1.5720 inches

Bore Diameter:

Between 0.1890 inches and 0.1910 inches

Outer Member Outside Diameter:

Between 0.6150 inches and 0.6350 inches

Bore Center To Shank End Distance:

Between 1.2200 inches and 1.2800 inches

Outer Member Width:

Between 0.2450 inches and 0.2550 inches

Inner Member Width:

Between 0.3070 inches and 0.3170 inches

Shank End To Shoulder Length:

0.6200 inches

Shank Thread Length:

0.6200 inches

Static Radial Load Rating:

900 pounds

Thread Diameter:

0.1900 inches

Features Provided:

Casehardened

Thready Qty Per Inch (tpi):

32

Material:

Steel rod end body

Material Specification:

6-6, (g-10/40/ms/5), caged 19207 mfr ref all material responses race insert

Surface Treatment:

Phosphate zinc rod end body

Surface Treatment Specification:

Dod-p-16232 military specification single treatment response rod end body

Style Designator:

Shouldered ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

spec.