

View Online at <https://aerobasegroup.com/nsn/3120-01-256-9292>

**Thread Class:**

2a

**Thread Direction:**

Left-hand

**Shank Style:**

Internally threaded

**Overall Length:**

Between 1.5520 inches and 1.5720 inches

**Bore Diameter:**

Between 0.1890 inches and 0.1910 inches

**Outer Member Outside Diameter:**

Between 0.6150 inches and 0.6350 inches

**Bore Center To Shank End Distance:**

Between 1.2200 inches and 1.2800 inches

**Outer Member Width:**

Between 0.2450 inches and 0.2550 inches

**Inner Member Width:**

Between 0.3070 inches and 0.3170 inches

**Shank End To Shoulder Length:**

0.6200 inches

**Shank Thread Length:**

0.6200 inches

**Static Radial Load Rating:**

900 pounds

**Thread Diameter:**

0.1900 inches

**Features Provided:**

Casehardened

**Thready Qty Per Inch (tpi):**

32

**Material:**

Steel rod end body

**Material Specification:**

6-6, (g-10/40/ms/5), caged 19207 mfr ref all material responses race insert

**Surface Treatment:**

Phosphate zinc rod end body

**Surface Treatment Specification:**

Dod-p-16232 military specification single treatment response rod end body

**Style Designator:**

Shouldered ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

spec.