NSN 3120-01-259-3706

Thrust Washer Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-259-3706

| Cross Sectional Shape: |
|--|
| Shouldered |
| Flange Thickness: |
| Between 0.2190 inches and 0.2210 inches |
| Outside Diameter: |
| Between 3.2350 inches and 3.2450 inches |
| Center Hole Shape: |
| Round |
| Diameter: |
| Between 2.1180 inches and 2.1200 inches |
| Overall Thickness: |
| Between 0.2730 inches and 0.2830 inches |
| Shank Outside Diameter: |
| Between 2.4970 inches and 2.5000 inches |
| Corner Shape: |
| Square all corners |
| Surface Finish: |
| 63.0 microinches right side of flange |
| Material: |
| Steel comp 440c |
| Material Specification: |
| Qq-s-763 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Ps13001 mfr ref single treatment response |
| Style Designator: |
| Round |
| Test Data Document: |
| 76301-ps21201 class b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |
| |