

View Online at <https://aerobasegroup.com/nsn/3120-01-259-9345>

Bore Diameter:

Between 0.3745 inches and 0.3750 inches

Lubrication Material:

Lubricant, dry film

Outer Member Outside Diameter:

Between 0.8120 inches and 0.8125 inches

Outer Member Width:

Between 0.3070 inches and 0.3170 inches

Inner Member Width:

Between 0.4040 inches and 0.4060 inches

Static Radial Load Rating:

21400 pounds

Hardness Rating:

37.0 rockwell c inner member

Material:

Steel comp 630 outer race member

Material Specification:

Ams 5687 assn standard single material response inner member

Style Designator:

Without insert or liner with staking groove

Test Data Document:

81349-mil-std-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-std-1949 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0