## NSN 3120-01-267-7558

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-267-7558

| Overall Length:  |
|--|
| 0.1120 inches  |
| Body Outside Diameter:   |
| Between 0.3756 inches and 0.3761 inches  |
| Body Inside Diameter:  |
| Between 0.2500 inches and 0.2515 inches  |
| Flange Outside Diameter:   |
| Between 0.4900 inches and 0.5100 inches  |
| Flange Width:  |
| Between 0.0570 inches and 0.0620 inches  |
| Corner Shape:  |
| Undercut left flange body corner   |
| Surface Finish:  |
| 100.0 microinches  |
| Material:  |
| Steel comp 4130 or steel comp 8630   |
| Material Specification:  |
| Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response |
| Surface Treatment:   |
| Cadmium and chromate   |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, class 2 federal specification single treatment response  |
| Style Designator:  |
| 22c solid, external flange one end   |
| Specification Data:  |
| 80205-nas77 professional/industrial association standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A045a0   |
| Mil-std (military Standard):   |
| Mil-s-6758 spec.   |
|  |