

View Online at <https://aerobasegroup.com/nsn/3120-01-271-1008>

**Bore Diameter:**

Between 0.8745 inches and 0.8750 inches

**Lubrication Material:**

Grease, mil-g-21164

**Outer Member Outside Diameter:**

Between 1.5620 inches and 1.5625 inches

**Outer Member Width:**

Between 0.6980 inches and 0.7080 inches

**Inner Member Width:**

Between 0.8730 inches and 0.8750 inches

**Static Radial Load Rating:**

62750 pounds

**Hardness Rating:**

56.0 rockwell c inner member

**Lubrication Feature:**

Perforation inner member and groove inner member

**Material:**

Steel comp e4340 outer race member or steel comp 4130 outer race member or steel comp 8630 outer race member

**Material Specification:**

Mil-s-5000 military specification 1st material response outer race member or mil-s-6758 military specification 2nd material response outer race member or mil-s-6050 military specification 3rd material response outer race member

**Surface Treatment:**

Cadmium outer race member

**Surface Treatment Specification:**

Qq-p-416, type 1, class 2 federal specification single treatment response outer race member

**Style Designator:**

Without insert or liner with staking groove

**Specification Data:**

96906-ms21154 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5000 spec.