## NSN 3120-01-276-5855

Mil-std (military Standard):

Mil-a-8625 spec.



Sleeve Bushing - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/3120-01-276-5855 **Overall Length:** 0.9000 inches **Body Outside Diameter:** 0.7000 inches **Body Inside Diameter:** Between 0.5630 inches and 0.5670 inches Flange Outside Diameter: Between 0.9930 inches and 0.9950 inches Flange Width: Between 0.1780 inches and 0.1820 inches **Corner Shape:** Square left flange outside right corner Surface Finish: 63.0 microinches outside diameter surface of flange **Special Features:** Flange stepped counterbored; first counterbore 0.814 in. Min - 0.820 in. Maximum dia, 0.083 in. Min - 0.093 in. Maximum I; second counterbore 0.692 in. Min - 0.696 in. Maximum dia, 0.092 in. L, 32.0 micrometers surface finish Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 3 military specification single treatment response **Style Designator:** 22c solid, external flange one end Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A045a0