

View Online at <https://aerobasegroup.com/nsn/3120-01-277-2406>

Slot Width:

0.1560 inches first and 0.1590 inches first

Slot Length:

0.2500 inches first and 0.2700 inches first

Overall Length:

Between 1.0700 inches and 1.1100 inches

Body Outside Diameter:

Between 0.7515 inches and 0.7520 inches

Body Inside Diameter:

Between 0.2500 inches and 0.2700 inches

Flange Outside Diameter:

Between 0.6900 inches and 0.7200 inches

Flange Width:

Between 0.0800 inches and 0.1000 inches

Corner Shape:

Square all corners

Hardness Rating:

28.0 rockwell c and 35.0 rockwell c

Antirotation/lubrication Type And Quantity:

2 slot

Special Features:

Id counterbored to 0.480 in. Diameter to 0.100 in. Lg at one end; keyway in od; od relieved to 0.720 in. Dia; 0.280 in. Lg at same end as counterbore

Material:

Steel comp 4140

Material Specification:

Mil-s-5626 military specification single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

D0d-p-16232, class 3 type m military specification single treatment response

Style Designator:

17c solid, plain, no outside flanges

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5626 spec.