NSN 3120-01-280-6933

Thrust Washer Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-280-6933

| Cross Sectional Shape: |
|---|
| Shouldered |
| Flange Thickness: |
| Between 0.0620 inches and 0.0720 inches |
| Outside Diameter: |
| 2.9850 inches |
| Center Hole Shape: |
| Round |
| Diameter: |
| Between 2.2525 inches and 2.2530 inches |
| Overall Thickness: |
| Between 0.2680 inches and 0.2700 inches |
| Shank Outside Diameter: |
| 2.5160 inches |
| Corner Shape: |
| Square second outside corner |
| Hardness Rating: |
| 33.0 rockwell c and 38.0 rockwell c |
| Surface Finish: |
| 20.0 microinches outside diameter surface of body |
| Material: |
| Steel comp e4340 |
| Material Specification: |
| Mil-s-5000 military specification single material response |
| Surface Treatment: |
| Oxide smallest outside diameter |
| Surface Treatment Specification: |
| Mil-c-13924, class 1 military specification single treatment response smallest outside diameter |
| Style Designator: |
| Round |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No . |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |
| Mil-s-5000 spec. |