NSN 3120-01-293-6697

A045a0

Mil-b-6946 spec.

Mil-std (military Standard):



Sleeve Bushing - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/3120-01-293-6697 **Overall Length:** 0.2320 inches **Body Outside Diameter:** Between 0.5006 inches and 0.5013 inches **Body Inside Diameter:** Between 0.3750 inches and 0.3765 inches Flange Outside Diameter: Between 0.6150 inches and 0.6350 inches Flange Width: Between 0.0570 inches and 0.0620 inches **Corner Shape:** Undercut left flange body corner Surface Finish: 100.0 microinches **Special Features:** Between champer length is 0.0250 inches and 0.0350; chamfer angle is 45/0 degrees; undercut width is 0.0150 inches; undercut depth is 0.0050 inches Material: Copper alloy 642 or copper alloy 630 **Material Specification:** Qq-c-465 federal specification 1st material response or mil-b-6946 military specification 2nd material response or ams 4640 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response Style Designator: 22c solid, external flange one end **Specification Data:** 80205-nas77 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: