

View Online at <https://aerobasegroup.com/nsn/3120-01-295-4767>

Shank Diameter:

Between 0.3090 inches and 0.3110 inches

Shank Style:

Hollow, unthreaded

Overall Length:

2.3430 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

Between 0.7710 inches and 0.7910 inches

Bore Center To Shank End Distance:

Between 1.5520 inches and 1.5720 inches

Outer Member Width:

Between 0.3370 inches and 0.3470 inches

Inner Member Width:

Between 0.4320 inches and 0.4370 inches

Shank Inside Diameter:

0.1870 inches

Shank Hole Length:

Between 1.0100 inches and 1.0700 inches

Static Radial Load Rating:

1720 pounds

Lubrication Feature:

Self-lubricating liner race liner

Material:

Plastic polytetrafluoroethylene race liner

Material Specification:

Qq-a-225/6, t6 federal specification single material response rod end body

Surface Treatment:

Anodize rod end body

Surface Treatment Specification:

Mil-a-8625, type 3 military specification single treatment response inner member

Style Designator:

Ball type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0

Mil-std (military Standard):

Mil-c-5541 spec.