

View Online at <https://aerobasegroup.com/nsn/3120-01-302-3587>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Bore Diameter:

Between 0.8745 inches and 0.8750 inches

Outer Member Outside Diameter:

Between 2.5520 inches and 2.5720 inches

Bore Center To Shank End Distance:

Between 4.4900 inches and 4.5100 inches

Outer Member Width:

Between 0.8700 inches and 0.8800 inches

Inner Member Width:

Between 1.1230 inches and 1.1250 inches

Shank End To Shoulder Length:

Between 2.4690 inches and 2.5620 inches

Shank Thread Length:

Between 2.4380 inches and 2.4690 inches

Thread Diameter:

1.0000 inches

Thready Qty Per Inch (tpi):

12

Special Features:

Item is self lubricated; has a dyflon plastic alloy liner; item is partof the link assembly, interconnect inboard elevator; used on elevator interconnect installation on cargo aircraft

Material:

Steel

Material Specification:

Mil-b-8948 military specification single material response

Style Designator:

Shouldered ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-b-8948 spec.