

View Online at <https://aerobasegroup.com/nsn/3120-01-302-3587>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Bore Diameter:**

Between 0.8745 inches and 0.8750 inches

**Outer Member Outside Diameter:**

Between 2.5520 inches and 2.5720 inches

**Bore Center To Shank End Distance:**

Between 4.4900 inches and 4.5100 inches

**Outer Member Width:**

Between 0.8700 inches and 0.8800 inches

**Inner Member Width:**

Between 1.1230 inches and 1.1250 inches

**Shank End To Shoulder Length:**

Between 2.4690 inches and 2.5620 inches

**Shank Thread Length:**

Between 2.4380 inches and 2.4690 inches

**Thread Diameter:**

1.0000 inches

**Thready Qty Per Inch (tpi):**

12

**Special Features:**

Item is self lubricated; has a dyflon plastic alloy liner; item is partof the link assembly, interconnect inboard elevator; used on elevator interconnect installation on cargo aircraft

**Material:**

Steel

**Material Specification:**

Mil-b-8948 military specification single material response

**Style Designator:**

Shouldered ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-b-8948 spec.