## NSN 3120-01-303-5696

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-303-5696

| Overall Languity   |
|--|
| Overall Length:  |
| 0.1800 inches  |
| Body Outside Diameter:   |
| 0.4326 inches  |
| Body Inside Diameter:  |
| Between 0.3125 inches and 0.3140 inches  |
| Flange Outside Diameter:   |
| 0.5630 inches  |
| Flange Width:  |
| Between 0.0550 inches and 0.0600 inches  |
| Corner Shape:  |
| Undercut left flange body corner   |
| Hardness Rating:   |
| 28.0 rockwell c and 37.0 rockwell c  |
| Surface Finish:  |
| 63.0 microinches outside diameter surface of body  |
| Material:  |
| Steel comp 630 or steel comp xm-12   |
| Material Specification:  |
| Ams 5643 assn standard 1st material response or ams 5659 assn standard 2nd material response |
| Surface Treatment:   |
| Cadmium and chromate   |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, class 3 federal specification single treatment response                    |
| Style Designator:  |
| 22c solid, external flange one end   |
| Specification Data:  |
| 84955-ks2211 manufacturers standard  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <u>-</u>   |
| Demilitarization:  |
| No   |
| Fiig:  |
| A045a0   |
|  |
|  |