NSN 3120-01-304-7928

Thrust Washer Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-304-7928

Shouldered Flange Thickness: Between 0.0180 inches and 0.0200 inches Outside Diameter: 0.2200 inches Center Hole Shape: Round Diameter: Between 0.0935 inches and 0.0937 inches Overall Thickness: Between 0.0300 inches and 0.0350 inches
Between 0.0180 inches and 0.0200 inches Outside Diameter: 0.2200 inches Center Hole Shape: Round Diameter: Between 0.0935 inches and 0.0937 inches Overall Thickness:
Outside Diameter: 0.2200 inches Center Hole Shape: Round Diameter: Between 0.0935 inches and 0.0937 inches Overall Thickness:
0.2200 inches Center Hole Shape: Round Diameter: Between 0.0935 inches and 0.0937 inches Overall Thickness:
Center Hole Shape: Round Diameter: Between 0.0935 inches and 0.0937 inches Overall Thickness:
Round Diameter: Between 0.0935 inches and 0.0937 inches Overall Thickness:
Diameter: Between 0.0935 inches and 0.0937 inches Overall Thickness:
Between 0.0935 inches and 0.0937 inches Overall Thickness:
Overall Thickness:
Between 0.0300 inches and 0.0350 inches
Dotwood C. Cook money and C. Cook money
Shank Outside Diameter:
0.1400 inches
Corner Shape:
Square all corners
Surface Finish:
63.0 microinches smallest outside diameter
Material:
Steel comp 303
Material Specification:
Astm a582 assn standard single material response
Surface Condition:
Ground
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Round
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0