## NSN 3120-01-304-9608

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-304-9608

view Offilite at https://aerobasegroup.com/hist//3120-01-304-3000
Overall Length:
Between 0.4120 inches and 0.4270 inches
Body Outside Diameter:
Between 0.5006 inches and 0.5013 inches
Body Inside Diameter:
Between 0.3750 inches and 0.3765 inches
Flange Outside Diameter:
Between 0.9900 inches and 1.0100 inches
Flange Width:
Between 0.0570 inches and 0.0620 inches
Corner Shape:
Undercut left flange body corner
Hardness Rating:
26.0 rockwell c and 33.0 rockwell c
Surface Finish:
100.0 microinches
Material:
Steel comp 4130 or steel comp 8630
Material Specification:
Mil-s-6758 military specification 1st material response or mil-t-6736 military specification 1st material response or mil-s-6050 military
specification 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class federal specification single treatment response
Style Designator:
22c solid, external flange one end
Specification Data:
78286-ss4091 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A045a0
Mil-std (military Standard):

Mil-s-6758 spec.