NSN 3120-01-305-7629

Sleeve Bushing - Page 1 of 1

Mil-std (military Standard):

Mil-s-6758 spec.



View Online at https://aerobasegroup.com/nsn/3120-01-305-7629 **Overall Length:** Between 0.3020 inches and 0.3170 inches **Body Outside Diameter:** Between 0.4381 inches and 0.4386 inches **Body Inside Diameter:** Between 0.3125 inches and 0.3140 inches Flange Outside Diameter: Between 0.6770 inches and 0.6970 inches Flange Width: Between 0.0570 inches and 0.0620 inches **Corner Shape:** Undercut left flange body corner Hardness Rating: 26.0 rockwell c and 33.0 rockwell c **Surface Finish:** 100.0 microinches Material: Steel comp 4130 or steel comp 8630 **Material Specification:** Mil-s-6758 military specification 1st material response or mil-t-6736 military specification 1st material response or mil-s-6050 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Style Designator:** 22c solid, external flange one end **Specification Data:** 78286-ss4091 manufacturers standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A045a0