## NSN 3120-01-307-8664

Sleeve Bushing - Page 1 of 1

Mil-s-6050 spec.



View Online at https://aerobasegroup.com/nsn/3120-01-307-8664

Overall Length:
Between 1.5950 inches and 1.6050 inches
Body Outside Diameter:
Between 0.4381 inches and 0.4386 inches
Body Inside Diameter:
Between 0.3125 inches and 0.3140 inches
Flange Outside Diameter:
Between 0.6770 inches and 0.6970 inches
Flange Width:
Between 0.0570 inches and 0.0620 inches
Corner Shape:
Square outside right corner
Hardness Rating:
26.0 rockwell c and 33.0 rockwell c
Material:
Steel comp 8630 or steel comp 4130
Material Specification:
Mil-s-6050 military standard single material response and mil-s-6758 military standard 1st material response and mil-t-6736 military
standard 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Style Designator:
22c solid, external flange one end
Specification Data:
78286-ss4091 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0
Mil-std (military Standard):