

View Online at <https://aerobasegroup.com/nsn/3120-01-315-5088>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

1.9740 inches

Bore Diameter:

Between 0.1895 inches and 0.1900 inches

Outer Member Outside Diameter:

Between 0.7969 inches and 0.8160 inches

Bore Center To Shank End Distance:

Between 1.5520 inches and 1.5720 inches

Outer Member Width:

Between 0.3320 inches and 0.3420 inches

Inner Member Width:

Between 0.4350 inches and 0.4375 inches

Shank Thread Length:

Between 0.9375 inches and 0.9990 inches

Static Radial Load Rating:

2360 pounds

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

39.0 rockwell c rod end body

Special Features:

Aircraft model hu25a exhaust and muffler installation

Material:

Steel comp 630 outer ring

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification 1st treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0