## NSN 3120-01-323-5619

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-323-5619

| Overall Length:  |
|--|
| 0.1262 inches  |
| Body Outside Diameter:   |
| Between 0.5631 inches and 0.5638 inches  |
| Body Inside Diameter:  |
| Between 0.4375 inches and 0.4390 inches  |
| Flange Outside Diameter:   |
| Between 0.6770 inches and 0.6970 inches  |
| Flange Width:  |
| Between 0.0570 inches and 0.0620 inches  |
| Corner Shape:  |
| Undercut left flange body corner   |
| Surface Finish:  |
| 100.0 microinches  |
| Material:  |
| Copper alloy 630 or copper alloy 642   |
| Material Specification:  |
| Astm b124 assn standard all material responses or astm b150 assn standard all material responses or astm b150 assn standard all material |
| responses or astm b283 assn standard 1st material response or ams 4640 assn standard 2nd material response                               |
| Style Designator:  |
| 22c solid, external flange one end   |
| Specification Data:  |
| 80205-nas77 professional/industrial association standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del>-</del>   |
| Demilitarization:  |
| No   |
| Fiig:  |
| A045a0   |
|  |
|  |
|  |
|  |