NSN 3120-01-325-3269

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-325-3269

| View Online at https://aerobasegroup.com/nsn/3120-01-325-3269 |
|--|
| Overall Length: |
| Between 0.3750 inches and 0.3800 inches |
| Body Outside Diameter: |
| Between 0.4381 inches and 0.4386 inches |
| Body Inside Diameter: |
| Between 0.3125 inches and 0.3140 inches |
| Corner Shape: |
| Square all corners |
| Hardness Rating: |
| 27.0 rockwell c and 32.0 rockwell c |
| Surface Finish: |
| 63.0 microinches outside diameter surface of body |
| Material: |
| Steel comp 630 or steel comp xm-12 |
| Material Specification: |
| Ams 5643 assn standard 1st material response or ams 5659 assn standard 2nd material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Style Designator: |
| 17c solid, plain, no outside flanges |
| Specification Data: |
| 84955-ks 2212 manufacturers standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |