

View Online at <https://aerobasegroup.com/nsn/3120-01-325-4651>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 2.3100 inches and 2.3400 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Outer Member Outside Diameter:

Between 0.8900 inches and 0.9100 inches

Bore Center To Shank End Distance:

Between 1.8650 inches and 1.8850 inches

Outer Member Width:

Between 0.3220 inches and 0.3320 inches

Inner Member Width:

Between 0.4350 inches and 0.4370 inches

Shank Thread Length:

Between 1.1560 inches and 1.2180 inches

Thread Diameter:

0.3125 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

39.0 rockwell c body and 42.0 rockwell c body

Material:

Steel comp 440c inner member

Material Specification:

Mil-s-5000 military standard single material response body

Surface Treatment:

Cadmium body

Surface Treatment Specification:

Qq-p-416, ty i, cl 2 federal specification single treatment response body

Style Designator:

Ball type

Thread Series Designator:

Unf

Specification Data:

81349-mil-b-81935 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.