

View Online at <https://aerobasegroup.com/nsn/3120-01-329-6732>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/bead and wrench flats and inspection hole

**Overall Length:**

1.7500 inches

**Bore Diameter:**

Between 0.1895 inches and 0.1915 inches

**Outer Member Outside Diameter:**

Between 0.7400 inches and 0.7600 inches

**Bore Center To Shank End Distance:**

Between 1.3650 inches and 1.3850 inches

**Outer Member Width:**

Between 0.3230 inches and 0.3330 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

0.7500 inches

**Inspection Hole Center To End Distance:**

Between 0.3070 inches and 0.3170 inches

**Shank Width Across Wrench Flats:**

Between 0.4580 inches and 0.4780 inches

**Thread Diameter:**

0.250 inches

**Features Provided:**

Flush lubrication fitting

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

60.0 rockwell c inner member

**Lubrication Feature:**

Groove external inner member

**Material:**

Steel rod end body

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0