

View Online at <https://aerobasegroup.com/nsn/3120-01-330-2416>

Thread Class:

3a

Thread Direction:

Left-hand

Shank Style:

Externally threaded

Overall Length:

2.4240 inches

Bore Diameter:

Between 0.3745 inches and 0.3750 inches

Outer Member Outside Diameter:

Between 0.9650 inches and 0.9800 inches

Bore Center To Shank End Distance:

Between 1.9280 inches and 1.9480 inches

Outer Member Width:

Between 0.3550 inches and 0.3700 inches

Inner Member Width:

Between 0.4950 inches and 0.5000 inches

Shank Thread Length:

1.2500 inches

Thread Diameter:

0.3750 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

35.0 rockwell c inner member

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Lubricant dry film inner member

Surface Treatment Specification:

Mil-I-46010 military specification single treatment response inner member

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0

Mil-std (military Standard):

Mil-I-46010 spec.