

View Online at <https://aerobasegroup.com/nsn/3120-01-334-6708>

**Shank Style:**

Externally threaded

**Overall Length:**

2.9105 inches

**Bore Diameter:**

Between 0.3745 inches and 0.3750 inches

**Lubrication Material:**

Lubricant, solid film, mil-I-46010

**Outer Member Outside Diameter:**

Between 0.9650 inches and 0.9800 inches

**Bore Center To Shank End Distance:**

Between 1.9280 inches and 1.9480 inches

**Outer Member Width:**

Between 0.3550 inches and 0.3700 inches

**Inner Member Width:**

Between 0.4950 inches and 0.5000 inches

**Shank Thread Length:**

1.2500 inches

**Static Radial Load Rating:**

10500 pounds

**Thread Diameter:**

0.3750 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

35.0 rockwell c inner member

**Special Features:**

Outer member id surface to be malcomized per p11ff1 cl-a ge spec

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Style Designator:**

Ball type

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0