
# NSN 3120-01-335-3016

Rod End Plain Bearing - Page 1 of 2

3b

24

Unjf





### **Thread Class: Thread Direction:** Left-hand Shank Style: Internally threaded w/hexagon end and inspection hole **Overall Length:** 2.4715 inches **Bore Diameter:** Between 0.3745 inches and 0.3750 inches **Outer Member Outside Diameter:** 1.1310 inches Bore Center To Shank End Distance: 1.9060 inches **Outer Member Width:** Between 0.3170 inches and 0.3270 inches **Inner Member Width:** Between 0.4040 inches and 0.4060 inches Shank Thread Length: 1.0000 inches **Inspection Hole Center To End Distance:** 0.4370 inches Shank Width Across Wrench Flats: Between 0.4910 inches and 0.5110 inches **Static Radial Load Rating:** 13400 pounds **Thread Diameter:** 0.3750 inches Thready Qty Per Inch (tpi): Hardness Rating: 55.0 rockwell c inner member and 62.0 rockwell c inner member **Special Features:** Keyslots in shank end Material: Steel comp e4340 rod end body **Material Specification:** Mil-s-5000 military specification single material response rod end body Style Designator: Ball type **Thread Series Designator:**

## NSN 3120-01-335-3016

Rod End Plain Bearing - Page 2 of 2



76301-st4-208 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A045a0

### Mil-std (military Standard):

Mil-s-5000 spec.

