## NSN 3120-01-335-3016

Rod End Plain Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-01-335-3016 **Thread Class: Thread Direction:** Left-hand **Shank Style:** Internally threaded w/hexagon end and inspection hole **Overall Length:** 2.4715 inches **Bore Diameter:** Between 0.3745 inches and 0.3750 inches **Outer Member Outside Diameter:** 1.1310 inches **Bore Center To Shank End Distance:** 1.9060 inches **Outer Member Width:** Between 0.3170 inches and 0.3270 inches **Inner Member Width:** Between 0.4040 inches and 0.4060 inches **Shank Thread Length:** 1.0000 inches **Inspection Hole Center To End Distance:** 0.4370 inches **Shank Width Across Wrench Flats:** Between 0.4910 inches and 0.5110 inches **Static Radial Load Rating:** 13400 pounds **Thread Diameter:** 0.3750 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 55.0 rockwell c inner member and 62.0 rockwell c inner member **Special Features:** Keyslots in shank end Material: Steel comp e4340 rod end body **Material Specification:** Mil-s-5000 military specification single material response rod end body **Style Designator:** Ball type **Thread Series Designator:** 

Unjf

## NSN 3120-01-335-3016

Rod End Plain Bearing - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

76301-st4-208 manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.