

View Online at <https://aerobasegroup.com/nsn/3120-01-335-3016>

**Thread Class:**

3b

**Thread Direction:**

Left-hand

**Shank Style:**

Internally threaded w/hexagon end and inspection hole

**Overall Length:**

2.4715 inches

**Bore Diameter:**

Between 0.3745 inches and 0.3750 inches

**Outer Member Outside Diameter:**

1.1310 inches

**Bore Center To Shank End Distance:**

1.9060 inches

**Outer Member Width:**

Between 0.3170 inches and 0.3270 inches

**Inner Member Width:**

Between 0.4040 inches and 0.4060 inches

**Shank Thread Length:**

1.0000 inches

**Inspection Hole Center To End Distance:**

0.4370 inches

**Shank Width Across Wrench Flats:**

Between 0.4910 inches and 0.5110 inches

**Static Radial Load Rating:**

13400 pounds

**Thread Diameter:**

0.3750 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

55.0 rockwell c inner member and 62.0 rockwell c inner member

**Special Features:**

Keyslots in shank end

**Material:**

Steel comp e4340 rod end body

**Material Specification:**

Mil-s-5000 military specification single material response rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unjf

**Specification Data:**

76301-st4-208 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5000 spec.