

View Online at <https://aerobasegroup.com/nsn/3120-01-335-3016>

Thread Class:

3b

Thread Direction:

Left-hand

Shank Style:

Internally threaded w/hexagon end and inspection hole

Overall Length:

2.4715 inches

Bore Diameter:

Between 0.3745 inches and 0.3750 inches

Outer Member Outside Diameter:

1.1310 inches

Bore Center To Shank End Distance:

1.9060 inches

Outer Member Width:

Between 0.3170 inches and 0.3270 inches

Inner Member Width:

Between 0.4040 inches and 0.4060 inches

Shank Thread Length:

1.0000 inches

Inspection Hole Center To End Distance:

0.4370 inches

Shank Width Across Wrench Flats:

Between 0.4910 inches and 0.5110 inches

Static Radial Load Rating:

13400 pounds

Thread Diameter:

0.3750 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

55.0 rockwell c inner member and 62.0 rockwell c inner member

Special Features:

Keyslots in shank end

Material:

Steel comp e4340 rod end body

Material Specification:

Mil-s-5000 military specification single material response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Specification Data:

76301-st4-208 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.