

View Online at <https://aerobasegroup.com/nsn/3120-01-335-7198>

Thread Class:

3a

Thread Direction:

Left-hand

Shank Style:

Externally threaded

Overall Length:

2.3250 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Outer Member Outside Diameter:

Between 0.8900 inches and 0.9100 inches

Bore Center To Shank End Distance:

Between 1.8650 inches and 1.8850 inches

Outer Member Width:

Between 0.3150 inches and 0.3350 inches

Inner Member Width:

Between 0.4320 inches and 0.4370 inches

Shank Thread Length:

1.0600 inches

Static Radial Load Rating:

7000 pounds

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

37.0 rockwell c inner member

Material:

Steel comp xm-12 rod end body

Material Specification:

Ams 5659 assn standard single material response rod end body

Surface Treatment:

Lubricant dry film inner member

Surface Treatment Specification:

Mil-I-46010 military specification single treatment response inner member

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-I-46010 spec.