

View Online at <https://aerobasegroup.com/nsn/3120-01-335-7199>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

2.6370 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Outer Member Outside Diameter:

Between 0.8900 inches and 0.9100 inches

Bore Center To Shank End Distance:

Between 2.1770 inches and 2.1970 inches

Outer Member Width:

Between 0.3150 inches and 0.3350 inches

Inner Member Width:

Between 0.4320 inches and 0.4370 inches

Shank Thread Length:

1.3600 inches

Thread Diameter:

0.3125 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

37.0 rockwell c inner member

Special Features:

Outer member i.D. Surface to be malcomized per p11tf1

Material:

Steel comp xm-12 rod end body

Material Specification:

Asms 5387 assn standard single material response inner member

Surface Treatment:

Lubricant dry film inner member

Surface Treatment Specification:

Mil-I-46010 military specification single treatment response inner member

Style Designator:

Ball type

Thread Series Designator:

Unjf

Specification Data:

07482-1584-59 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-I-46010 spec.