

View Online at <https://aerobasegroup.com/nsn/3120-01-335-7199>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

2.6370 inches

**Bore Diameter:**

Between 0.3120 inches and 0.3125 inches

**Outer Member Outside Diameter:**

Between 0.8900 inches and 0.9100 inches

**Bore Center To Shank End Distance:**

Between 2.1770 inches and 2.1970 inches

**Outer Member Width:**

Between 0.3150 inches and 0.3350 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

1.3600 inches

**Thread Diameter:**

0.3125 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

37.0 rockwell c inner member

**Special Features:**

Outer member i.D. Surface to be malcomized per p11tf1

**Material:**

Steel comp xm-12 rod end body

**Material Specification:**

Asms 5387 assn standard single material response inner member

**Surface Treatment:**

Lubricant dry film inner member

**Surface Treatment Specification:**

Mil-I-46010 military specification single treatment response inner member

**Style Designator:**

Ball type

**Thread Series Designator:**

Unjf

**Specification Data:**

07482-1584-59 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-I-46010 spec.