

View Online at <https://aerobasegroup.com/nsn/3120-01-336-2298>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 2.5850 inches and 2.6050 inches

**Bore Diameter:**

Between 0.3745 inches and 0.3750 inches

**Outer Member Outside Diameter:**

Between 1.1210 inches and 1.1410 inches

**Bore Center To Shank End Distance:**

Between 2.0200 inches and 2.0400 inches

**Outer Member Width:**

Between 0.3170 inches and 0.3270 inches

**Inner Member Width:**

Between 0.4040 inches and 0.4060 inches

**Shank End To Shoulder Length:**

Between 1.1560 inches and 1.2180 inches

**Shank Thread Length:**

1.1870 inches

**Static Radial Load Rating:**

13000 pounds

**Thread Diameter:**

0.3750 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

39.0 rockwell c body and 42.0 rockwell c body

**Lubrication Feature:**

Self-lubricating liner outer race member

**Keyway Dimension:**

0.0930 inches external keyway width and 0.0980 inches external keyway width

**Special Features:**

Item is self-aligning

**Material:**

Steel

**Material Specification:**

Mil-s-5000 military specification single material response

**Style Designator:**

Shouldered ball type

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5000 spec.