

View Online at <https://aerobasegroup.com/nsn/3120-01-336-2298>

Thread Class:

3a

Thread Direction:

Left-hand

Shank Style:

Externally threaded

Overall Length:

Between 2.5850 inches and 2.6050 inches

Bore Diameter:

Between 0.3745 inches and 0.3750 inches

Outer Member Outside Diameter:

Between 1.1210 inches and 1.1410 inches

Bore Center To Shank End Distance:

Between 2.0200 inches and 2.0400 inches

Outer Member Width:

Between 0.3170 inches and 0.3270 inches

Inner Member Width:

Between 0.4040 inches and 0.4060 inches

Shank End To Shoulder Length:

Between 1.1560 inches and 1.2180 inches

Shank Thread Length:

1.1870 inches

Static Radial Load Rating:

13000 pounds

Thread Diameter:

0.3750 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

39.0 rockwell c body and 42.0 rockwell c body

Lubrication Feature:

Self-lubricating liner outer race member

Keyway Dimension:

0.0930 inches external keyway width and 0.0980 inches external keyway width

Special Features:

Item is self-aligning

Material:

Steel

Material Specification:

Mil-s-5000 military specification single material response

Style Designator:

Shouldered ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.