

View Online at <https://aerobasegroup.com/nsn/3120-01-336-2299>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/hexagon end and inspection hole

**Overall Length:**

1.7510 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Outer Member Outside Diameter:**

Between 0.8170 inches and 0.8370 inches

**Bore Center To Shank End Distance:**

Between 1.3280 inches and 1.3480 inches

**Outer Member Width:**

Between 0.2550 inches and 0.2650 inches

**Inner Member Width:**

Between 0.3410 inches and 0.3430 inches

**Shank Thread Length:**

0.7500 inches

**Inspection Hole Center To End Distance:**

Between 0.2920 inches and 0.3320 inches

**Shank Width Across Wrench Flats:**

Between 0.3650 inches and 0.3770 inches

**Thread Diameter:**

0.3125 inches

**Thready Qty Per Inch (tpi):**

24

**Keyway Dimension:**

0.1100 inches external keyway depth and 0.1150 inches external keyway depth

**Special Features:**

Item is self-aligning, self-lubricating; heat treatment is in accordance with mil-h-6875

**Material:**

Steel comp 4340 body

**Material Specification:**

Mil-s-5000 military specification single material response body

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Style Designator:**

Ball type

**Thread Series Designator:**

Unjf

**Specification Data:**

81349-mil-b-81935/5b government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5000 spec.