

View Online at <https://aerobasegroup.com/nsn/3120-01-336-2299>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/hexagon end and inspection hole

Overall Length:

1.7510 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

Between 0.8170 inches and 0.8370 inches

Bore Center To Shank End Distance:

Between 1.3280 inches and 1.3480 inches

Outer Member Width:

Between 0.2550 inches and 0.2650 inches

Inner Member Width:

Between 0.3410 inches and 0.3430 inches

Shank Thread Length:

0.7500 inches

Inspection Hole Center To End Distance:

Between 0.2920 inches and 0.3320 inches

Shank Width Across Wrench Flats:

Between 0.3650 inches and 0.3770 inches

Thread Diameter:

0.3125 inches

Thready Qty Per Inch (tpi):

24

Keyway Dimension:

0.1100 inches external keyway depth and 0.1150 inches external keyway depth

Special Features:

Item is self-aligning, self-lubricating; heat treatment is in accordance with mil-h-6875

Material:

Steel comp 4340 body

Material Specification:

Mil-s-5000 military specification single material response body

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Style Designator:

Ball type

Thread Series Designator:

Unjf

Specification Data:

81349-mil-b-81935/5b government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.