## NSN 3120-01-339-0286

Sleeve Bearing - Page 1 of 1

A045a0



| View Online at https://aerobasegroup.com/nsn/3120-01-339-0286  |
|--|
| Overall Length:  |
| Between 0.1970 inches and 0.2120 inches  |
| Body Outside Diameter:   |
| Between 0.3755 inches and 0.3761 inches  |
| Body Inside Diameter:  |
| Between 0.2390 inches and 0.2410 inches  |
| Flange Outside Diameter:   |
| Between 0.6600 inches and 0.6800 inches  |
| Flange Width:  |
| Between 0.0570 inches and 0.0620 inches  |
| Corner Shape:  |
| Undercut left flange body corner   |
| Hardness Rating:   |
| 28.0 rockwell c outer layer and 37.0 rockwell c outer layer  |
| Surface Finish:  |
| 63.0 microinches outside diameter surface of body  |
| Material:  |
| Steel comp 630 outer layer   |
| Material Specification:  |
| Ams 5643 assn standard single material response outer layer  |
| Surface Treatment:   |
| Cadmium outside diameter surface of body and chromate outside diameter surface of body                     |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, class 2 federal specification single treatment response outside diameter surface of body |
| Style Designator:  |
| 22c solid, external flange one end   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |