

View Online at <https://aerobasegroup.com/nsn/3120-01-342-7760>

**Thread Class:**

3b

**Thread Direction:**

Left-hand

**Shank Style:**

Internally threaded w/hexagon end and inspection hole

**Overall Length:**

1.7780 inches

**Bore Diameter:**

Between 0.1895 inches and 0.1900 inches

**Outer Member Outside Diameter:**

Between 0.7960 inches and 0.8160 inches

**Bore Center To Shank End Distance:**

Between 1.3650 inches and 1.3850 inches

**Outer Member Width:**

Between 0.3320 inches and 0.3420 inches

**Inner Member Width:**

Between 0.4350 inches and 0.4370 inches

**Shank Thread Length:**

0.7500 inches

**Inspection Hole Center To End Distance:**

0.3745 inches

**Shank Width Across Wrench Flats:**

Between 0.4270 inches and 0.4390 inches

**Static Radial Load Rating:**

2360 pounds

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

55.0 rockwell c inner member and 62.0 rockwell c inner member 28.0 rockwell c race insert and 37.0 rockwell c race insert 39.0 rockwell c rod end body and 42.0 rockwell c rod end body

**Material:**

Steel comp 440c inner member steel comp 630 race insert plastic polytetrafluoroethylene race liner steel comp e4340 rod end body

**Material Specification:**

Ams 5630 assn standard single material response inner member ams 5643 assn standard single material response race insert mil-s-5000 military specification single material response rod end body

**Surface Treatment:**

Cadmium rod end body and chromate rod end body

**Surface Treatment Specification:**

Qq-p-416, cl 2 federal specification all treatment responses rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5000 spec.