

View Online at <https://aerobasegroup.com/nsn/3120-01-345-0610>

Bore Diameter:

Between 0.6245 inches and 0.6250 inches

Outer Member Outside Diameter:

Between 1.1870 inches and 1.1875 inches

Outer Member Width:

Between 0.4950 inches and 0.5050 inches

Inner Member Width:

Between 0.6230 inches and 0.6250 inches

Hardness Rating:

56.0 rockwell c inner member 27.0 rockwell c outer race member and 36.0 rockwell c outer race member

Lubrication Feature:

Groove inner member and perforation inner member groove outer race member and perforation outer race member

Special Features:

Prepacked with mil-g-21164 grease

Material:

Steel comp 440c inner member steel comp e4340 outer race member or steel comp 4130 outer race member or steel comp 8630 outer race member

Material Specification:

Ams 5630 assn standard single material response inner member mil-s-5000 military specification single material response outer race member or mil-s-6758 military specification single material response outer race member or mil-s-6050 military specification single material response outer race member

Surface Treatment:

Chromium inner member cadmium outer race member and chromate outer race member

Surface Treatment Specification:

Qq-c-320, cl 2 federal specification single treatment response inner member qq-p-416, type 2, cl 2 federal specification single treatment response outer race member

Style Designator:

Without insert or liner with staking groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.