

View Online at <https://aerobasegroup.com/nsn/3120-01-345-0610>

**Bore Diameter:**

Between 0.6245 inches and 0.6250 inches

**Outer Member Outside Diameter:**

Between 1.1870 inches and 1.1875 inches

**Outer Member Width:**

Between 0.4950 inches and 0.5050 inches

**Inner Member Width:**

Between 0.6230 inches and 0.6250 inches

**Hardness Rating:**

56.0 rockwell c inner member 27.0 rockwell c outer race member and 36.0 rockwell c outer race member

**Lubrication Feature:**

Groove inner member and perforation inner member groove outer race member and perforation outer race member

**Special Features:**

Prepacked with mil-g-21164 grease

**Material:**

Steel comp 440c inner member steel comp e4340 outer race member or steel comp 4130 outer race member or steel comp 8630 outer race member

**Material Specification:**

Ams 5630 assn standard single material response inner member mil-s-5000 military specification single material response outer race member or mil-s-6758 military specification single material response outer race member or mil-s-6050 military specification single material response outer race member

**Surface Treatment:**

Chromium inner member cadmium outer race member and chromate outer race member

**Surface Treatment Specification:**

Qq-c-320, cl 2 federal specification single treatment response inner member qq-p-416, type 2, cl 2 federal specification single treatment response outer race member

**Style Designator:**

Without insert or liner with staking groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5000 spec.