# NSN 3120-01-349-1868

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-349-1868

# **Overall Length:**

Between 0.6407 inches and 0.6557 inches

## Body Outside Diameter:

Between 1.4593 inches and 1.4603 inches

# Body Inside Diameter:

Between 1.1255 inches and 1.1265 inches

# Flange Outside Diameter:

1.8650 inches

## End Application:

A-10 acft

Flange Width:

Between 0.0887 inches and 0.0937 inches

# Corner Shape:

Undercut left flange body corner

# Surface Finish:

63.0 microinches outside diameter surface of body

# Special Features:

Static radial limit load is 31, 430 lbs.; static axial limit load is 66, 820 lbs; item has self lubricating liner bonded to sleeve i.D. And sleeve face

# Material:

Aluminum alloy 7075

#### Material Specification:

Qq-a-200/11 federal specification single material response

#### Surface Treatment:

Anodize

#### Surface Treatment Specification:

Mil-a-8625, type i military specification single treatment response

#### Style Designator:

22c solid, external flange one end

#### Shelf Life:

N/a

#### Unit Of Measure:

```
--
```

## Demilitarization:

No

Fiig:

## A045a0

Mil-std (military Standard):

Mil-a-8625 spec.