

View Online at <https://aerobasegroup.com/nsn/3120-01-349-4264>

Bore Diameter:

Between 0.1895 inches and 0.1900 inches

Outer Member Outside Diameter:

Between 0.5620 inches and 0.5625 inches

Outer Member Width:

Between 0.2130 inches and 0.2230 inches

Inner Member Width:

Between 0.2790 inches and 0.2810 inches

Static Radial Load Rating:

2800 pounds

Hardness Rating:

56.0 rockwell c inner member 27.0 rockwell c outer race member and 36.0 rockwell c outer race member

Lubrication Feature:

Groove inner member and perforation inner member

Material:

Steel comp e52100 inner member or steel comp 440c inner member copper alloy 642 outer race member or copper alloy 630 outer race member

Material Specification:

Ams 5630 assn standard 2nd material response inner member astm b124 assn standard all material responses outer race member or astm b150 assn standard all material responses outer race member or astm b283 assn standard 1st material response outer race member

Surface Treatment:

Chromium inner member cadmium outer race member

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response outer race member

Style Designator:

Without insert or liner

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0