

View Online at <https://aerobasegroup.com/nsn/3120-01-353-5435>

Thread Class:

3a

Thread Direction:

Left-hand

Shank Style:

Externally threaded

Overall Length:

1.9650 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

Between 0.7960 inches and 0.8160 inches

Bore Center To Shank End Distance:

Between 1.5520 inches and 1.5720 inches

Outer Member Width:

Between 0.3320 inches and 0.3420 inches

Inner Member Width:

Between 0.4350 inches and 0.4370 inches

Shank Thread Length:

Between 0.9370 inches and 0.9990 inches

Thread Diameter:

0.3120 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

55.0 rockwell c inner member and 62.0 rockwell c inner member 28.0 rockwell c race insert and 37.0 rockwell c race insert 39.0 rockwell c rod end body and 42.0 rockwell c rod end body

Special Features:

Lock washer slot in shank

Material:

Steel comp 440c inner member steel comp 630 race insert plastic polytetrafluoroethylene race liner steel comp 4340 rod end body

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0