

View Online at <https://aerobasegroup.com/nsn/3120-01-356-3229>

**Bore Diameter:**

Between 0.4370 inches and 0.4375 inches

**Lubrication Material:**

Grease, mil-g-21164

**Outer Member Outside Diameter:**

Between 0.9057 inches and 0.9062 inches

**Outer Member Width:**

Between 0.3380 inches and 0.3480 inches

**Inner Member Width:**

Between 0.4350 inches and 0.4370 inches

**Static Radial Load Rating:**

18850 pounds

**Hardness Rating:**

56.0 rockwell c inner member 27.0 rockwell c outer race member and 36.0 rockwell c outer race member

**Lubrication Feature:**

Groove external outer member perforation inner member groove internal inner member groove internal outer member perforation outer race member

**Material:**

Steel comp 440c inner member steel comp e4340 outer race member or steel comp 4130 outer race member or steel comp 8630 outer race member

**Material Specification:**

Ans 5630 assn standard single material response inner member mil-s-6758 military specification 1st material response outer race member or mil-s-6758 military specification 2nd material response outer race member or mil-s-6050 military specification 3rd material response outer race member

**Surface Treatment:**

Chromium inner member cadmium outer race member

**Surface Treatment Specification:**

Qq-c-320, cl 2 type 1 federal specification single treatment response inner member or qq-c-320, cl 2 type 2 federal specification single treatment response inner member qq-p-416, ty1 cl 2 federal specification single treatment response outer race member

**Style Designator:**

Without insert or liner with staking groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-6758 spec.