

View Online at <https://aerobasegroup.com/nsn/3120-01-356-3229>

Bore Diameter:

Between 0.4370 inches and 0.4375 inches

Lubrication Material:

Grease, mil-g-21164

Outer Member Outside Diameter:

Between 0.9057 inches and 0.9062 inches

Outer Member Width:

Between 0.3380 inches and 0.3480 inches

Inner Member Width:

Between 0.4350 inches and 0.4370 inches

Static Radial Load Rating:

18850 pounds

Hardness Rating:

56.0 rockwell c inner member 27.0 rockwell c outer race member and 36.0 rockwell c outer race member

Lubrication Feature:

Groove external outer member perforation inner member groove internal inner member groove internal outer member perforation outer race member

Material:

Steel comp 440c inner member steel comp e4340 outer race member or steel comp 4130 outer race member or steel comp 8630 outer race member

Material Specification:

Ans 5630 assn standard single material response inner member mil-s-6758 military specification 1st material response outer race member or mil-s-6758 military specification 2nd material response outer race member or mil-s-6050 military specification 3rd material response outer race member

Surface Treatment:

Chromium inner member cadmium outer race member

Surface Treatment Specification:

Qq-c-320, cl 2 type 1 federal specification single treatment response inner member or qq-c-320, cl 2 type 2 federal specification single treatment response inner member qq-p-416, ty1 cl 2 federal specification single treatment response outer race member

Style Designator:

Without insert or liner with staking groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.