

View Online at <https://aerobasegroup.com/nsn/3120-01-359-7144>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Bore Diameter:**

Between 0.9995 inches and 1.0000 inches

**Lubrication Material:**

Lubricant, solid film, mil-l-8937

**End Application:**

Pacer special

**Outer Member Outside Diameter:**

1.5000 inches

**Bore Center To Shank End Distance:**

3.3600 inches

**Outer Member Width:**

0.4240 inches

**Inner Member Width:**

Between 0.4940 inches and 0.5000 inches

**Shank End To Shoulder Length:**

2.3400 inches

**Shank Thread Length:**

2.3400 inches

**Thread Diameter:**

0.6250 inches

**Thready Qty Per Inch (tpi):**

18

**Lubrication Feature:**

Groove outer race member

**Special Features:**

Item has a keyway that is .1250 inches in dia.

**Material:**

Steel comp xm-12

**Material Specification:**

Ams 5659 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002c military specification single treatment response

**Style Designator:**

Shouldered flange type

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5002c spec.