

View Online at <https://aerobasegroup.com/nsn/3120-01-359-7144>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Bore Diameter:

Between 0.9995 inches and 1.0000 inches

Lubrication Material:

Lubricant, solid film, mil-l-8937

End Application:

Pacer special

Outer Member Outside Diameter:

1.5000 inches

Bore Center To Shank End Distance:

3.3600 inches

Outer Member Width:

0.4240 inches

Inner Member Width:

Between 0.4940 inches and 0.5000 inches

Shank End To Shoulder Length:

2.3400 inches

Shank Thread Length:

2.3400 inches

Thread Diameter:

0.6250 inches

Thready Qty Per Inch (tpi):

18

Lubrication Feature:

Groove outer race member

Special Features:

Item has a keyway that is .1250 inches in dia.

Material:

Steel comp xm-12

Material Specification:

Ams 5659 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002c military specification single treatment response

Style Designator:

Shouldered flange type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5002c spec.